4E 4164

B.Tech. IV Semester (Main) Examination, June/July - 2015 Computer Science and Engineering 4CS5A Fundamental of Communication

Time: 3 Hours

Maximum Marks: 80

Min. Passing Marks: 26

Instructions to Candidates:

Attempt any five questions, selecting one question from each unit. All questions carry equal marks. (Schematic diagrams must be shown wherever necessary. Any data you feel missing suitably be assumed and stated clearly. Units of quantities used/calculated must be stated clearly.)

Unit - 1

- (a) What are modulation & its need? Explain the working principle of envelope detector for demodulation of AM wave using suitable diagrams.
 - (b) The Antenna current of an AM Broadcast transmitter, modulated to a depth of 40% by an audio sine wave is 11 ampere. It is Increase to 12 amp.

 As a result of sinusoidal modulation by another audio sine wave. What is the modulation index due to second wave.

 (8)

OR

1. (a) Explain the role of pre-emphasis and de-emphasis in FM system. (8)

(b) Find the modulation index, modulating frequency, carrier frequency and maximum deviation of FM wave represented by the voltage equation e=12Sin (6x10⁸ t+5 sin 1250t). What power will be the FM dissipate in a 10 ohm resister. (8)

Unit - II

2. (a) State the Sampling theorem for band limited signal. What is aliasing and how it is reduced? (8)

		lollow	ing signals	
			$\frac{1}{2\pi}$ Cos $(4000\pi t)$ Cos $(1000\pi t)$ sinC $(100\pi t) + 3$ SinC ² $(60\pi t)$	(8)
			OR	
2.	(a)	Descri	be modulation & Demodulation method for PAM.	(8)
	(b)	Explai	n natural and flat top sampling.	(8)
			Unit - III	
			Unit-111	
3.	a)		is companding? Explain a μ -law and A-law for non-uniform zation.	(8)
	b)		der a sinusoidal signal $m(t) = A\cos Wmt$ applied to a delta modulate tep size Δ . Show that the slope overload distortion will occurs if	
		$A > \frac{\Delta}{W_m}$	$\frac{1}{\sqrt{T_s}}$	(8)
			, ° OK	
3.	a)	Draw	the block diagram of ROM system and discuss each block in deta	il. (8)
	b)		in T-1 carrier system (digital) using suitable diagram. Also calculate & bandwidth of it. rtuonline.com	e (8)
4.	(a)		Unit-IV t sequence 1110110011 is to be transmitted using different coding ques (a) unipolar RZ and NRZ (b) polar RZ and NRZ.	
		Draw a	all the wave form for given bit sequence.	(8)
	(b)	What	is Inter symbol interference ? Explain Nyquist criteria for zero IS	I.
				(8)
			OR	
4.	a)	-	in the generation, coherent and non-coherent detection of Binary F susing suitable diagrams.	FSK (8)
4E	4164	+	(2)	

(b) Determine the nyquist sampling rate and nyquist sampling interval for the

b) Explain the generation and detection of QPSK signals using suitable diagrams (8)

Unit-V

- 5. (a) What is PN sequence and How it is generated? What is maximum length sequence?
 - (b) What is Direct sequence spread spectrum modulation.

(8

OR

- 5. (a) What is frequency hop. Spread spectrum? How does FHSS provide secured communication? (8)
 - (b) Define processing gain in a CDMA system. How is the capacity calculated for a CDMA system. (8)